

Airflow

Fresh air volume		
Indoor	Type	ECM centrifugal
	CFM	125 - 350
	Available ESP	N/A
	Supply connection	Integrated front
	Return connection	Integrated bottom
	Speeds	Low, med, high, boost, auto
	Filter	MERV 3
Outdoor	Type	ECM centrifugal
	CFM	135 - 383
	Available ESP	0.45" WC
	Intake connection	6" round
	Exhaust connection	
	Speeds	Low, med, high, auto

General

Compressor		
Type		BLDC twin rotary inverter
Refrigerant	Type	R32
	Oz.	23.97
Oil	Type	Fv50s
Controls		
Basic functionality	Dependent on controller	
WiFi	Optional module available	
Dry contact	Yes	
Power outage restart	Auto-on based on last setting	
Modes		
Operation	Cool+ fresh air, cool only, heat+ fresh air, heat only, auto	
Restricted modes	Heat only, cool only, temperature limiting	
Timers	Dependent on controller	
Condensate		
Pipe	Size	3/4" Outside diameter
	Material	Rubber

Sound

Sound		
Indoor	dB(A)	27-43
	STC	40
	OITC	35
Outdoor	dB(A)	28-55

Dimensions

Physical data		
Dimensions	Net	43.1" W x 33.2" D x 12.3" H
	Net	170 lb
Weight	Gross	190 lb
	Finish	RAL 9003 signal white
Cabinet	Material	Steel