

Electrical

Electrical		115V	230V
General			
Volt range		103-127	180-253
Hz/ phase		60 Hz singe phase	
Power supply		Hardwire or LCDI	
Power factor (%)		0.96	
Input power (standby)	W	10.8	10.8
Input power (off mode)		1.5	1.5
Cooling (nominal)	A	5.8	2.9
Cooling (max)		15.7	7.8
Heat Pump Only			
Heating - heat pump only (nom.)	A	6.1	3.1
Heating - heat pump only (max)		16.5	8.3
Heat Pump + 900 W Elec Heat			
Heating - heat pump +900 W Elec Heat (nom.)	A	13.9	7.0
Heating - heat pump +900 W Elec Heat (max)		24.3	12.2
Heat Pump + 1,800 W Elec Heat			
Heating - heat pump only (nom.)	A	-	10.6
Heating - heat pump only (max)		-	16.1

		115V	230V
Motors			
Compressor	RLA	A	9.5
	LRA		4.7
Indoor ECM fan motor	W (max)	A	180
	F.L.A.		0.8
	HP		0.24
Outdoor ECM fan motor	W (max)	A	190
	F.L.A.		0.8
	HP		0.25

		115V	230V
Circuit breakers			
Heat Pump Only	MCA	20	10
	Recommended breaker size	A	20
	MOCP	35	20
Heat Pump + 900 W Elec Heat	MCA	30	15
	Recommended breaker size	A	30
	MOCP	40	25
Heat Pump + 1,800 W Elec Heat	MCA	N/A	20
	Recommended breaker size	A	N/A
	MOCP	N/A	30

		115V	230V
LCDI Power Cord			
Heat Pump Only	Amps	20	15
	Plug Type	5-20P	6-15P
Heat Pump + 900 W Elec Heat	Amps	N/A*	15
	Plug Type		6-15P
Heat Pump + 1,800 W Elec Heat	Amps		20
	Plug Type		6-20P

*LDCI cord not available in 115V above 20A